

Rockfon® Color-all™

UP TO
0.95
 NRC

Features & Benefits

- 34 exclusive colors for acoustic ceiling and wall solutions to inspire and enhance your interior design scheme
- Smooth surface
- Excellent sound absorption (NRC = 0.85 - 0.95)
- Fire Performance - Class A
- Optimal design freedom due to the variety of edges (lay-in, tegular and concealed) and colors

Applications

- Office
- Industry
- Healthcare
- Retail
- Classroom
- Restaurant
- Reception
- Auditorium



Rockfon ceiling tiles are manufactured using advanced stone wool technology. All stone wool tiles benefit from:



High Acoustic Absorption



Fire Performance - Class A



Moisture and Sag Resistance



Smooth, Modern Aesthetics

Materials and Resources (MR)

- Waste Management Planning
- Interiors Life Cycle Impact Reduction
- Environmental Product Declarations
- Sourcing of Raw Materials
- Material Ingredients
- Waste Management

Indoor Environmental Quality (EQ)

- Low-Emitting Materials ✓
- ✓ Interior Lighting ✓
- ✓ Acoustic Performance ✓

Recycled Content 41%



Standard Panels

Edge Designation	Item Number	Modular Size (nominal)*	NRC	Fire Class	Light Reflectance	Sag Resistance (relative humidity)	Low VOC	lbs/sqft	sqft/carton	
	SQ	11100	2' x 2' x 5/8"	0.90	A	Color Dependant	up to 100%	✓	0.47	112
	SQ	11101	2' x 4' x 5/8"	0.90	A	Color Dependant	up to 100%	✓	0.47	112
	SL	11250	2' x 2' x 3/4"	0.95	A	Color Dependant	up to 100%	✓	0.69	40
	SL	11251	2' x 4' x 3/4"	0.95	A	Color Dependant	up to 100%	✓	0.69	80
	SLN	11200	2' x 2' x 3/4"	0.95	A	Color Dependant	up to 100%	✓	0.69	40
	SLN	11201	2' x 4' x 3/4"	0.95	A	Color Dependant	up to 100%	✓	0.69	80
	CDX	11600	2' x 2' x 7/8"	0.95	A	Color Dependant	up to 100%	✓	0.75	40
	CDX	11601	2' x 4' x 7/8"	0.95	A	Color Dependant	up to 100%	✓	0.75	80

Recycled content values for our stone wool tiles and panels are based on 2020 production averages of a standard 2' X 2' tile and based on their primary production location.

* Refer to the Rockfon® Module System brochure for module tile sizes.

Minimum Order Quantities for Rockfon® Color-All™

All Rockfon Color-All Square Edge (SQ) 2'x2' and 2'x4' tiles = 300 sqft minimum. Minimums do not apply to Color-all Standard Program.** For any other sizes, please contact Rockfon Customer Service.

SL, SL, SLN, and CDX edges in all dimensions in all 34 Color-all colors = 6,000 sqft. Minimums do not apply to Color-all Standard Program.**

(Different edges and dimensions can be mixed in the same color. The quantity per dimension/edge must be 1,000 sqft and the total quantity must be 6,000 sqft.)


** Minimum order quantities do not apply to matching Color-All grid products and 4 Color-all Standard Program Colors: 701 Stone, 706 Concrete, 723 Hemp, 709 Charcoal. For further questions please contact Rockfon Customer Service.

15/16" Suspension Systems	9/16" Suspension Systems
200, 1200 and Fire Rated systems	4000, 4200, 4500 and Fire Rated systems
<p>SQ - Square Lay-In SL - Square Tegular CDX - Fully Concealed</p>	<p>SLN - Square Tegular Narrow</p>

Rockfon® Color-all™ Standard Program Colors



Light reflectance: 0.04



Light reflectance: 0.16




Light reflectance: 0.45




Light reflectance: 0.55

Please refer to Rockfon® Color-all™ Standard Program Datasheet for more details.

Additional Rockfon® Color-all™ Colors




Light reflectance: 0.36




Light reflectance: 0.55




Light reflectance: 0.70




Light reflectance: 0.08



Light reflectance: 0.21




Light reflectance: 0.55



Light reflectance: 0.70



Light reflectance: 0.05




Light reflectance: 0.12




Light reflectance: 0.34




Light reflectance: 0.70




Light reflectance: 0.04



Light reflectance: 0.08




Light reflectance: 0.34




Light reflectance: 0.51

The actual color of the ceiling tiles may deviate slightly from printed colors due to the texture of the surface and the underlying color of stone wool. Samples of the colored surfaces are available upon request.

Additional Rockfon® Color-all™ Colors



Light reflectance: 0.22



Light reflectance: 0.22




Light reflectance: 0.29




Light reflectance: 0.49




Light reflectance: 0.51




Light reflectance: 0.04




Light reflectance: 0.30



Light reflectance: 0.07



Light reflectance: 0.33




Light reflectance: 0.33



Light reflectance: 0.44




Light reflectance: 0.07



Light reflectance: 0.34



Light reflectance: 0.58



Light reflectance: 0.74

The actual color of the ceiling tiles may deviate slightly from printed colors due to the texture of the surface and the underlying color of stone wool. Samples of the colored surfaces are available upon request.



Rockfon® Color-all™ Properties

Material

Stone wool (Mineral Wool) ceiling tiles with factory applied latex paint on glass scrim surface
 ASTM E1264 CLASSIFICATION: Type XX - Stone wool base with membrane-faced overlay, Pattern G



Fire Performance

Surface burning characteristics:
 UL723 (ASTM E84) Flame Spread Index: 5-15
 Smoke Developed Index (UL Labeled): 0
Flame Spread Index is color dependant



Sustainability

Many of Rockfon stone wool acoustic solutions are GREENGUARD Gold low VOC certified and meet the State of California's Department of Public Health Services Standard Practice for Specification Section 01350 (California Section 01350) for testing chemical emissions.

Selected potential applications: LEED, WELL, CHPS, Green Globes, BREEAM Int. and CALGreen

- ✓ GREENGUARD Gold available*
- ✓ Environmental Product Declaration available*

* Applicable to all edge types



Cleaning

Vacuum



Environment

41% recycled content. Recycled content based on European manufacturing.



Warranty

30-Year Limited Product Warranty
 See rockfon.com



Thermal Insulation

R Value (BTU Units): 2.2 - 3.1
 RSI Value (Watts Units): 0.39 - 0.54



Hygiene

Stone wool provides no sustenance to microorganisms



Tile Directionality

Rockfon Color-all™ tiles are directional and must be installed according to backside arrow direction. The arrow can be turned 180°, not 90°



GREENGUARD Gold Certified
 for Office and Educational
 Environments



CERTIFIED Environmental
 Product Declaration

060123

Rockfon

4849 S. Austin Ave.
 Chicago, IL 60638 USA

2023 | Subject to alterations in range and product technology without prior notice. Rockfon accepts no responsibility for printing errors.
 © ROCKWOOL A/S 2022. All rights reserved.

® denotes a trademark that is registered in the United States of America.

Tel. +1-800-323-7164
 cs@rockfon.com
 rockfon.com